



# AIR ACTUATED BOTTLE JACKS

18122C & 18202C are made with welded construction which eliminates contaminants from entering hydraulic system and provides leak free operation.



**18125**  
12 Ton Capacity



**18122C**  
12 Ton Capacity



**18202C**  
20 Ton Capacity



**18205**  
20 Ton Capacity



**18209**  
20 Ton Capacity  
(Low profile)



**18302C**  
30 Ton Capacity



**18502**  
50 Ton Capacity



**18992**  
100 Ton Capacity

- Effortless air operation will greatly reduce operator fatigue and speed up the efficiency of garage work
- A compact yet powerful Air Turbo Motor U.S. Patent No. 5,341,723 is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,946,912, a built-in by-pass device protects hydraulic system from over pumping damage
- Versatile "Quick Connector" design provides for easy removal of air hose from air motor allowing compact storage or remote operation
- All air bottle jacks have chrome plated rams

Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension. Screw	Base Size Length	Base Size Width	G.W.
18122C	12 Ton	9-1/2"	18-1/2"	5-1/2"	3-1/2"	8"	6-1/2"	31 Lbs.
18125			18-5/8"	6"	3-1/8"	8-7/8"	5-3/4"	29 Lbs.
18202C	20 Ton	9-3/4"	18-3/4"	5-1/8"	3-7/8"	8-1/2"	7-1/4"	40 Lbs.
18205		9-1/2"	18-1/4"	5-5/8"	3-1/8"	9-1/4"	6-3/4"	39 Lbs.
18209		8-1/8"	15-1/2"	4"	3-3/8"	8-1/2"	7-1/4"	35 Lbs.
18302C	30 Ton	11"	18-1/8"	7-1/8"	N/A	10-1/4"	8-1/4"	63 Lbs.
18502	50 Ton	12"	19"	7"		10-7/8"	7-3/8"	139 Lbs.
18992	100 Ton		18-1/8"	6-1/8"		12-5/8"	9-3/8"	218 Lbs.



## JACK PAD

- Provides stable surface for bottle and air bottle jacks
- 20 Ton capacity
- Light weight
- Non-skid surface



90020



<i>Model</i>	<i>Capacity</i>	<i>Dimensions (L X H X W)</i>	<i>G.W.</i>
90020	20 Ton	12" X 12" X 1"	5 Lbs.